

Grip superior eco

Description

Blown, pre-stretched, 30% recycled content

	Spec	Tolerance	Method
Film Width	400mm 480m	Nominal +/- 40mm	In house method
Roll Length	0.892kg film only	Nominal +/-1%	
Individual Film Weight	(Net) 0.158kg	Nominal +/-10%	
Core Weight	6 mic	Nominal +/- 2%	
Spot Thickness	6 mic	Nominal +/-20%	
Average Thickness	Not less than 50g	Nominal +/- 10%	
Dart Impact Strength	90kGN/m	Not less than 50g	
Longitudinal Endurance	200kGN/m	Nominal +/-10%	
Traverse Endurance	>30%	Nominal +/-10%	
Recycled Polymer Content		Nominal +/-2%	
Roll Profile	Oscillated with folded edges		
Core	25mm Notched	Nominal +/- 1mm	
Colours & additives		Natural clear colour – slightly murky due to the recycled content	
Product composition		A base component of LLDPE (Linear low-density polyethylene) & LDPE (low density polyethylene) with a super blend of Polyisobutylene, Butene, Hexene, and Metallocene additives.	
Storage		The product should be stored in a dry place out of direct sunlight at a temperature not greater than 25°C and not less than 5°C to maintain stability.	
Qty on pallet		360 rolls (8rolls/box) 45 boxes per pallet.	
Food usage		The main polymers are in compliance with the food contact legislation, however the PIB is not in compliance with food contact legislation.	