

Description:

Water Activated, Hand-held Taper

	Spec	Additional Info
Taper Unit		
Unit Weight	Loaded - 2.140kg	
Size of Unit	Length - 255mm, Height - 195mm, Width - 135mm	
Tank Capacity	Approx. 390ml	
Pre-set mode lengths	300mm, 400mm, 500mm, 600mm, 700mm, 800mm, 900mm	
Speed	1 - 5 modes	
Replaceable foam roller	Yes	
Product Finish	ABS Plastic	
Battery		
Voltage	7.4V	
Capacity	2000mAh	
Operational Ambient Range	Charge: 0°C~45°C Discharge: -20°C~60°C	
Weight	0.143kg	
Approved UL Standard	UL 2054	Safety of Household and Commercial batteries
Charge time	Approx. 3 hours	
Runtime	Approx. 8 hours	

Product

Each Taper will be sold with 1 battery, charging point and different plug adapters.

Storage

The product should be stored in a dry place out of direct sunlight at a temperature not greater than 25°C as the battery may overheat which will reduce the performance or shorten the service life.

QTY on pallet

48 units - 1 unit and battery per box

Caution:

- Do not use the battery if it gives off an odour, generates heat, becomes discoloured or deformed, or appears abnormal in any way.
- If the battery leaks or emits an odour, immediately remove it from the proximity of any exposed flame
- If the battery leaks and electrolyte gets in your eyes, do not rub them. Instead, rinse them with clean running water and immediately seek medical attention.
- If a device is not used for an extended period, the battery should be removed and stored in a cool, dry place. Otherwise, resting or reduced performance may occur.