

PVC STANDARD

| Component Material | Description | Color | Thickness (µm) |
|--------------------|----------------|----------------------------|---------------------|
| Carrier | PVC | Transparent | 32 |
| Adhesive | Natural rubber | Translucent / White /brown | 19 + ----- 51 |

2. Product advantages:

A PVC carrier in combination with a natural rubber adhesive

3. Main application:

Carton boxes sealing tape, suited for (semi)-automatic machines.

4. Features

- Initial adhesion/tack ● ● ●
- Final adhesion ● ● ●
- Dimensional stability ● ● ●

5. Suitability on

- High energy plastics: PVC, PC, ABS, ... ● ● ●
- Low energy plastics: PE, PP, ... ● ● ●
- Metal ● ● ●
- Paper/Cardboard ● ● ●

● ● ● very good ● ● good ● limited

6. Technical data

- Peel adhesion to SS
- Tensile Strength
- Elongation

Testing method

- Afera 5001
- Afera 5004
- Afera 5004

Unit

- N/25mm
- N/25mm
- %

Value

- > 3.5
- > 110
- > 48

7. Storage conditions:

Store in a cool dry place away from sunlight and direct heat sources. Storage temperature : 23°C ± 2°C Relative humidity : 50% RH ± 5% As far as the storage conditions are respected, the product is guaranteed 12 months.