

Budget PP tape Acryl



Product description:

No-noise adhesive tape with a solvent-free, water-based acrylic adhesive. The high-tack formula ensures strong adhesion, making it ideal for sealing medium-weight boxes with manual dispensers or automatic carton sealing machines. UV and aging resistant for long-lasting performance.

FEATURES

-  No noise unwinding
-  Solvent free
-  UV resistant



High Tack formula

MAIN APPLICATIONS

-  Medium weight box sealing
-  Manual dispensers
-  Automatic carton sealing machines BROWN

BACKING MATERIAL

BIAXIALLY ORIENTED

POLYPROPYLENE

TYPE OF ADHESIVE

WATER BASED ACRYLIC

COLOURS

-  BROWN
-  WHITE
-  TRANSPARENT

TECHNICAL DATA	Metric	Values	Test method
Backing thickness	µm	28	AFERA 5006
Total thickness	µm	52	AFERA 5006
Adhesion to steel	N/cm	2.6	AFERA 5001
Tensile strength	N/cm	45	AFERA 5004
Elongation at break	%	160	AFERA 5004

Technical Information, Storage, and Product Use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and direct light. The storage temperature must be between 15°C and 30°C, with relative humidity between 40% and 60%. For storage temperatures outside these ranges, recondition the product to the levels described above.

The technical data shown in the data sheets represent the average of analyses obtained during normal production. Aging may cause variations in some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data provided have a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Stipar declines all responsibility for direct damage and consequences resulting from improper use of the product.

It is advisable to verify the product's conformity in relation to specific usage conditions.